

 **BELLTEC** *Industries, Inc.*

Belltec Max M Series Auger Drives
4 Year Warranty



Drill holes fast, where others fail.

Belltec Max M Series Auger Drives

The **Belltec Max Series** hydraulic auger drives are available in three models for systems operating between 10 and 35 GPM and 2000 to 3000 PSI. The Max Series planetary outperforms and has heavier components than any of its competitors. First tubular frame on the market with the largest and strongest cradle. Mounting frame mounts to all modern skid loaders with the universal attach system. The **Max Series** units are ideal for all drilling applications from dirt to solid rock and concrete when paired with the correct H Series auger.

No Case Drain Hoses Required

Features:

- Heaviest in Class Planetary Gearbox with No Snaps Rings
- Heavy Duty Nut Prevents Shaft Pull Out
- Heavy Duty Motors with High Pressure Seal
- Heavy Duty Hexagon Housing
- 2" Hex Output Shaft

MODEL M-200		ORDER NUMBER 113028	
MAXIMUM OUTPUT TORQUE		2000 FT-LBS	
RECOMMENDED FLUID FLOW		10-20 GPM	
MAXIMUM PRESSURE-CONTINUOUS		3000 PSI	
RECOMMENDED MAX AUGER DIA-DIRT30 INCHES	
OUTPUT SPEED		OUTPUT TORQUE	
FLOW	SPEED	PRESSURE	TORQUE
GPM	RPM	PSI	Lb-Ft
10	48	2000	1339
12	55	2200	1480
14	64	2400	1607
16	73	2600	1740
18	82	2800	1874
20	92	3000	2008

MODEL M-300		ORDER NUMBER 113029	
MAXIMUM OUTPUT TORQUE		3000 FT-LBS	
RECOMMENDED FLUID FLOW		15-30 GPM	
MAXIMUM PRESSURE-CONTINUOUS		3000 PSI	
RECOMMENDED MAX AUGER DIA-DIRT36 INCHES	
OUTPUT SPEED		OUTPUT TORQUE	
FLOW	SPEED	PRESSURE	TORQUE
GPM	RPM	PSI	Lb-Ft
15	47	2000	1958
18	56	2200	2066
22	68	2400	2350
26	81	2600	2546
28	87	2800	2742
30	93	3000	2937

MODEL M-350		ORDER NUMBER 113030	
MAXIMUM OUTPUT TORQUE		3000 FT-LBS	
RECOMMENDED FLUID FLOW		20-35 GPM	
MAXIMUM PRESSURE-CONTINUOUS		3000 PSI	
RECOMMENDED MAX AUGER DIA-DIRT36 INCHES	
OUTPUT SPEED		OUTPUT TORQUE	
FLOW	SPEED	PRESSURE	TORQUE
GPM	RPM	PSI	Lb-Ft
20	51	2000	2388
24	62	2500	2985
26	67	3000	3582
28	72		
30	77		
35	90		



BELLTEC Industries, Inc.

Post Office Box 270 • Belton, Texas 76513

1-800-242-9410 • Fax 254-939-9408

www.belltec.net • sales@belltec.net